

Measure wide range of electrical parameters with the CMP-40X series Clamp Meters

Measurement functions

- AC current measurement up to 400 A
- DC current measurement up to 400 A (**CMP-401 only**)
- DC and AC voltage measurement up to 600 V
- resistance measurement
- continuity test with acoustic signalling (beeper) for resistance below 50 Ω
- temperature measurement (Fahrenheit or Celsius)
- frequency measurement
- capacitance measurement (**CMP-401 only**)
- diode test

Overview

Sonel CMP-401 and CMP-400 Clamp Meters are designed to hard work in arduous measuring conditions. A special housing, covered with an elastomer coating, provides protection against drops and mechanical damages. CMP-401 and CMP-400 are the first choice for those who expect the device to be reliable at work in industrial and residential environments.

Designed for specialists

- industrial and commercial electricians
- plant maintenance
- facility maintenance
- electrical contractors
- utility technicians
- HVACR specialists


CAT III
600 V
CAT IV
300 V
 **IP40**




Special features

- non-contact neon lamp
- safe, insulated measurement clamp
- reinforced, impact resistant enclosure
- automatic selection of ranges with the capability of switching over to the manual selection mode
- HOLD function, allowing for freezing the result on the display
- large and easy to read LCD display with backlight
- relative measurement function
- indication of range overflow



Facilitating the measurements

The AC-16 adapter expands the application of the clamp meter. With the ratio x1 and x10, 230 V AC of voltage and max 16 A of current, the adapter can be applied with any type of clamp meter.

DC current measurement (CMP-401 only)

Range	Resolution	Accuracy
4.00 A	0.01 A	±(2.5% m.v. + 5 digits)
400.0 A	0.1 A	± (2.8% m.v. + 5 digits)

AC current measurement

Range	Resolution	Accuracy	
		CMP-400	CMP-401
4.000 A	0.001 A	±(2.5% m.v. + 12 digits)	-
40.00 A	0.01 A	±(2.8% m.v. + 8 digits)	±(2.5% m.v. + 8 digits)
400.0 A	0.1 A	±(2.8% m.v. + 8 digits)	±(2.8% m.v. + 5 digits)

• frequency range: 50...60 Hz

DC voltage measurement

Range	Resolution	Accuracy
400.00 mV	0.01 mV	±(0.8% m.v. + 2 digits)
4.000 V	0.001 mV	±(1.5% m.v. + 2 digits)
40.00 V	0.01 V	
400.0 V	0.1 V	±(2% m.v. + 2 digits)
600 V	1 V	

AC voltage measurement

Range	Resolution	Accuracy	
		CMP-400	CMP-401
400.00 mV	0.01 mV	±(1.5% m.v. + 30 digits)	±(1.5% m.v. + 30 digits)
4.000 V	0.001 mV	±(1.8% m.v. + 8 digits)	±(1.5% m.v. + 2 digits)
40.00 V	0.01 V		
400.0 V	0.1 V	±(2.5% m.v. + 8 digits)	±(2% m.v. + 2 digits)
600 V	1 V		

• frequency range: 50...60 Hz

Resistance measurement

Range	Resolution	Accuracy
100.0 Ω	0.1 Ω	±(1.0% m.v. + 4 digits)
4.000 kΩ	0.001 kΩ	±(1.5% m.v. + 2 digits)
40.00 kΩ	0.01 kΩ	
400.0 kΩ	0.1 kΩ	±(2.5% m.v. + 3 digits)
4.000 MΩ	0.001 MΩ	
40.00 MΩ	0.01 MΩ	±(3.5% m.v. + 5 digits)

Frequency measurement

Range	Accuracy
10 Hz...10 kHz	±(1.5% m.v. + 2 digits)

Temperature

Range	Resolution	Accuracy *
-20...+760°C	1°C	±(3% m.v. + 5°C)
-4...+1400°F	1°F	±(3% m.v. + 9°F)

* probe accuracy not included

Capacitance measurement (CMP-401 only)

Range	Resolution	Accuracy
40.00 nF	0.01 nF	±(4% m.v. + 20 digits)
400.0 nF	0.1 nF	±(3% m.v. + 5 digits)
4.000 μF	0.001 μF	
40.00 μF	0.01 μF	±(4% m.v. + 10 digits)
100.0 μF	0.1 μF	

Abbreviation „m.v.“ used in the specification of measurement means a measured value.

Technical specification

power supply of the meter	9 V battery, type 6LR61
display	4000 readings, backlit LCD
continuity test	threshold 50 Ω , measurement current <0.5 mA
diode test	typical measurement current 0.3 mA typical voltage of open circuit 1.5 V DC
indication of low battery charge	'BAT' symbol is displayed
indication of range overflow	'OL' symbol is displayed
frequency of measurements	2 readings per second, nominal
temperature sensor	K-type temperature probe
interior clamp diameter	opening 1.2" (30 mm)
input impedance	10 M Ω (V DC and V AC)
AC bandwidth	50...400 Hz (A AC and V AC)
auto-off timeout	approx. 30 minutes
dimensions	197 mm x 70 mm x 40 mm
weight	183 g
compliance with standards	EN 61010-1, EN 61010-2-032

Nominal operating conditions

operating temperature range	5...40°C
operating humidity	max. 80% up to 31°C decreasing linearly to 50% at 40°C
storage temperature	-20...+60°C at humidity <80%
operating altitude	max. 2000 m

Standard accessories



test lead with probe
for CMM/CMP (set)
WAPRZCMP1



Temperature measurement
type K probe
WASONTEMK
adapter
WAADATEMK



6LR61 9 V battery

Additional accessories



AC-16 line splitter
(faciliates current
measurements)
WAADAAC16



S1 carrying case
WAFUTS1



Temperature measurement
probe (K-type, bayonet)
WASONTEMP
probe (K-type, metal)
WASONTEMK2